








TYPE 1



TYPE 2



PCB LAYOUT

型号: KH-XH-(2-10)A-W

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2501-02AW	2.50	7.50
A2501-03AW	5.00	10.00
A2501-04AW	7.50	12.50
A2501-05AW	10.00	15.00
A2501-06AW	12.50	17.50
A2501-07AW	15.00	20.00
A2501-08AW	17.50	22.50
A2501-09AW	20.00	25.00
A2501-10AW	22.50	27.50
A2501-11AW	25.00	30.00
A2501-12AW	27.50	32.50
A2501-20AW	47.50	52.50

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	贺骏驹 2013. 07. 01	料号 PART NO.	A2501-NAW	版本 REV.	A
			$X \pm 0.25$	$X' \pm 2'$	审核 CHECK	赖积任 2013. 07. 03	品名 TITLE	TJC3弯针 WAFER DIP TYPE	页次 SHEET	1/1
			$.X \pm 0.20$	$.X' \pm 1'$	核准 APPROVAL	张松强 2013. 07. 05	客户料号 CLTM. NO.	KH-XH-4A-W	深圳市金航标电子有限公司 www.kinghelm.com.cn 0755-83044319	
			$.XX \pm 0.15$	$.XX' \pm 0.5'$	单位 UNITS	MM	比例 SCALE	1:1		
			$.XXX \pm 0.10$	$.XXX' \pm 0.5'$						